

AKROGUARD

Seamless Air/Weather Barrier



AkroGuard does double duty as an air & water resistive barrier (WRB) wrapping the structure seamlessly. Nothing hugs the curves and contours of windows and architectural features like AkroGuard. It withstands wall movement better and has self sealing properties.

Unlike house wraps, AkroGuard liquid applied membrane does not tear, require nailing or stapling. Peel-and-stick membranes have tacky surfaces that can stick together and can't be pulled apart when handling, creating wrinkles and pockets where air and water can get trapped. AkroGuard prevents all of these tricky installation problems while being faster and easier to install.

The benefits don't stop here, AkroGuard has built in UV resistance allowing it to be exposed to the elements for up to six months. When AkroGuard is used with other Omega wall system products, a WRB-to-finish warranty is available for up to 18 years. The Omega integrated wall warranty lets you build with confidence.



Building codes continue to be more stringent in all climates for energy efficiency, requiring air & water barriers in new construction. AkroGuard liquid membrane requires less time and less labor to apply because it can be rolled-on, troweled-on, or sprayed-on. It is easier to install around windows, curves and decorative features providing seamless protection. Liquid membranes create an air-tight seal, which is why even some makers of WRB coated sheathing require liquid flashing to seal joints. AkroGuard has been extensively tested and complies with ICC-ES Acceptance Criteria for Water-Resistive Coatings (AC208) and meets the ASTM requirements as an air barrier.

Ideal for use under:

Stucco &
EIFS



Wood
Siding



Vinyl & Cement
Board Siding



Masonry
& Stone



Metal
Panels



Features:

- Vapor-permeable weather barrier
- Self sealing properties with air-tight application
- Excellent elongation properties
- UV resistant
- 18 year integrated wall warranty*

Benefits:

- Seamless protection
- WRB Weather-proofed building
- Can be left exposed to the elements for up to 6 months
- Resistant to tearing or punctures
- No need for mechanical attachments
- Reduce utility cost of the building

*When used with Omega wall construction products

Fast & Easy Application Methods

Spray-On



Roll-On



Trowel-On

